

creating beautiful environments SOLID SURFACES



NEONNEX

Decorating a space is all about adorning a dream. Every space, be it office or home, speaks of your persona. It's all about your attitude and style reflected in the most beautiful way. Now is the time to make it beautiful and durable for eternity with Neonnex premium acrylic solid surface. It's an enchanting solution that's both alluring and long-standing. Available in wide spectrum of colors, it creates a vibrant and visually appealing world all around you.

Easy to cut, shape, mold, route, and thermoform in to threedimensional shapes, it lets you live your dream in 'real'. Resisting moisture, pollutants, and bacteria, Neonnex[™] is an ideal solution for every space making it hygienic and safe. Neonnex[™] 100% Acrylic Solid Surface, the versatile, acrylic decorative surfacing material is composed of high-performance acrylic resins and natural minerals to enhance its appearance and performance. Our manufacturing process uses high-tech & computerized controlled continues casting equipment and world class materials for making world class product. Thus architects, designers, contractors or private individuals, Neonnex[™] Solid Surface appeals to everyone wishing to work with a high capacity material and aesthetically pleasing.

Features:

- Warm to the touch
- Non- porous
- Easy to clean
- Resistant to physical pressure
- Resistant to corrosive household assets
- Resistant to heat

- Long life
- Completely hygienic
- Easily repairable
- Easily processed and combined by seamless method
- Thermoforming
- Wide choice of color solutions

 Reonnex[™] is designed for indoor application only, and not recommended for exterior use. It may undergo changes in color and easily damaged when used in outdoor environment

 Neonnex[™] is not recommended for use as a flooring product due to the possibility of scratching

Neonnex is not recommended for use as a nooring product due to the possibility of scratching







Residential

Get ready to explore endless design possibilities to adorn your dream home. Let your imagination come to full fore and be sure to transform it in to a beautiful reality. Blending aesthetic appeal with unmatched strength, it's an eternal bond of elegance and performance.



Table Top • Wall Cladding • Wardrobe Shutter • BedCladding • Pillar Cladding • False ceiling • Murals• Furniture Cladding • Wall Paneling with CNC cut









Bathroom

An ideal choice for bathrooms, these moisture-proof solutions help you bask in the beauty of your bathrooms for an eternity. It's three-dimensional formability gives room for multiple applications like vanities, sinks, cabinets and window sills. The stain-free attribute is an added joy!

Vanity • Vanity Counter • Wall Cladding • Shower Tray • Shower Cubical • Bath Tub • Vanity Furniture • Door Jams & Window Sills • Mirror Frames • Washroom Partitions





Kitchen

Now enjoy a worry-free cooking experience. Forget about spills, stains and dirt. Neonnex[™] solid surface as non-stick y surfaces will make your cooking experience more delightful. As distinct as your personality, your kitchen will speak of your elegant taste.





•Kitchen Counter top • Back Splash with Covering • Dado wall • Sink Bowls • Kitchen Island Top • Serving Counter • Kitchen Shutters • Chopping Board • Dust Bin













Commercial

Highly durable, elegant and versatile. It is a perfect choice for spaces that receives huge foot fall. An ideal solution for public spaces, shopping centers and other commercial applications. It's non-porous and hygienic qualities makes it appropriate choice for hotels, healthcare and areas where hygiene is of utmost priority.

Reception desk • Wall Partition • Featured/Designer Wall • Column Cladding • Airline Check in Counters • Display Boxes • Dust Bin • Seating's in the lounge area• Working Counter • Lift Lobby Cladding • Luggage Racks • Food Court Areas • Planters • Urinal Partition • Conference Table • Signage • Handrail





Retail

Think beyond counters and perceive it as a beautiful part of your space. It's a creativity meets functionality for places where first impression is the last impression.



Display Units
Display counters
Signage
Designer/Customized Wall panels
POP Units
Light Fixtures
Cash Counters
Kiosks







Healthcare

Healthcare industry that demands highest hygienic standards, this is an ideal choice. Being non-porous, it doesn't let pathogens inhibiting bacterial growth. Fighting against impacts and spilling that ruin the beauty of surface, it promises beauty for longetivity.

OT wall cladding
 OT Ceiling
 OT Door Jams
 Scrub Vanities
 Vanity Counters
 Baby Bath
 Nursing Counter
 Laboratory Tops
 Hygiene
 Surfaces
 Crash Guards
 Storage racks

Care & Maintenance

Celaning Kitchen counter tops and other Neonnex[™]Surfaces

Neonnex[™] is a durable and repairable product that will last for many years with simple care. Follow these instructions to preserve your Neonnex[™] solid surface products.

Everyday Care

General cleaning of your NeonnexTM solid surfaces can be done by wiping the surface with a damp cloth or sponge, then dry with soft cloth or paper towel to prevent spotting especially in area with hard water.

Basic Stains

Clean with an ammonia-based product such as house hold glass cleaner or commercially available non abrasive spray -on cleaners for solid surface products. Wipe dry with a soft cloth or paper towel to prevent spotting.

Stubborn Stain and Minor Scratches

There are over 75 colors available in NeonnexTM and each color can be supplied with a different type of finish by a NeonnexTM certified fabricator/installer. Dark color in counter top surface particularly show signs of use, such as scratches and soap residue, more readily than light colored solid surfaces materials. Therefore gloss finish generally requires additional maintenance and care to retain its original luster. Different cleaning techniques are required to remove stubborn stain and minor scratches depending on the type of finish and color as detailed in the following instructions.

Note: please contact your certified fabricator / installer if you are uncertain which type of finish is applied to your Neonnex[™] solid surfaces. DO NOT ATTEMPT TO REPAIR DEEP SCRATCHES, CHIPS OR BURNS, CONTACT A CERTIFIED NEONNEX[™] FABRICATOR/ INSTALLER FOR REPAIR.

Matt finish is the standard finish delivered by your certified fabricator/installer. It is a low or no-sheen finish and is recommended in all high use areas.

Stain Finish has a slightly higher sheen than of matt and requires more attention depending on the frequency of use and area of application.

Gloss finish is a higher and reflective sheen that requires additional care and maintenance. It is important to note that a gloss finish, especially on a dark color, will require more care than a Matt/Satin finish. Therefore be sure not to apply the same method or process recommended for a Matt/Satin finish when caring for a gloss finish. Repeat the procedure shown below if stain persists. Contact your certified fabricator/installer for further assistance.

DO NOT USE ABRASIVE CLEANERS AND PADS OF ANY TYPE ON A GLOSS FINISH PLEASE CONTACT YOUR NEONNEX™ RETAILER / DEALER FOR MORE INFORMATION.

After completing the above procedure, rinse with clear water and wipe dry using a soft cloth or paper towel to prevent spotting. To enhance the visual color clarity and hide minor scuffs, apply counter top magic cleanser (available at any hardware store or supermarket) and wipe away excess with a soft cloth.

Preventing Damage

Minor damage that may accidentally occur is most often repairable by a Neonnex[™] certified fabricator/ installer or repair expert. However be sure follow these guidelines to prevent damage to your Neonnex[™] surface.

HEAT: Neonnex[™] solid surfaces have excellent heat resistant properties compared to other countertop materials. However placing hot pans, as well as some heat-generating appliances such as electric grill or deep-fryers can damage the surface, always use a hot pad or a trivet with rubber feet to protect Neonnex[™] Avoid subjecting Neonnex[™] solid surfaces to extreme hot temperatures.

CHEMICAL: Avoid exposing Neonnex[™] solid surfaces to strong chemicals such as paint removers, acetone and oven cleaners. Surfaces exposed to these chemicals should be promptly flushed with water contact spots that may require extensive repairs. Remove nail polish with non-acetone based nail polish remover and flush with water.

SCRATCHES: Never cut or chop directly on a Neonnex[™] solid surfaces. Always use a cutting / chopping board.


FRACTURES : Avoid standing on countertops or dropping heavy objects on the surface.

Note: Gloss Reduction, Scratching and staining on solid surface incurred over time due to use is not a manufacturing defect but is considered normal wear and tear. The forgoing is not covered under the NeonnexTM. If your NeonnexTM products is accidentally nicked or deeply scratched, please contact your retailer /dealer or NeonnexTM certified fabricator/installer for advice about the most effective method or repair most repairs are relatively quick and simple when performed by an experienced professional (service/nominal charge may apply).


For more detailed information, contact your Neonnex[™] dealer / retailer or visit us at: w w w.neonnex.com

Disclaimer:

The information contained herein is provided by Neonnex[™] for information purpose only and should be used by individuals with technical experience and knowledge in the respective area. Neonnex[™] does not assume any responsibility whatsoever related to use of the information. Exclusion of the implied warranties may not apply in certain jurisdictions.



confirmation shall be based on actual material.



Green Leaf



Master Distributor •India •Pakistan •Sri Lanka •Nepal •Bangladesh



901, Mauryansh Elanza, Nr. Parekh Hospital, Shyamal Cross Road, Satellite, Ahmedabad-15 (Gujarat) India. Ph.: 079 4032 7583 / +91 97129 83859 Tele Fax: 079 66627230 e-mail: info@neonnex.com, care@neonnex.com Visit us: www.neonnex.com

Dealer:

Description	Neonnex [™] Result	Test Method
Density	1.72 g/cm ²	ASTM D-792A
Hardness Test	91 Rockell M Scale	ASTM D-785
	63 Barcoll Impressor	ASTM D-2583
Pencile Hardness (HRM)	92	KS D 6711
Water Absorption	0.03%	ASTM D-570
Thermal Expansion Coef. (OC)	2.10 x 10 ⁻⁵	ASTM D-696
Ignition Test	38	ASTM D-2863
Tensile Strength	6500 psi	ASTM D-638
Elongation	0.73%	ASTM D-638
Flexural Strength	10,000 psi	ASTM D-790
Impact Resistence - 8ft, 0.5 lb	Unbreakable	ANSI Z-124.6
Color Stability	No-change, 200 hrs	NEMA LD-3
Luster Stable Resistance	Uninfluential	NEMA LD-3-3.3
Water Resistance, g/1000 cycl	0.05	ASTM D-4060
High Temperature Resistance	Uninfluential	NEMA LD-3-3.6
Stain Resistance	Uninfluential	ANSI Z-124.6
Boiling Water Resistance	Uninfluential	NEMA LD-3-3.5
Chemical Resistance	Uninfluential	ANSI Z-124.6
Food Zone Acceptability	Accepted / Listed	NSF 51
Fungi & Bacteria	No Growth	ASTM G-21
Flammability	Class 1	UBC 8-1
●Flame Speed	0 - 25	ASTM E-84
Smoke Density	<25	ASTM E-84

Technical Specification

	Granite	Quartz	Stainless Steel	Laminate	Neonnex [™] Solid Surface
Resists heat	\checkmark			Ø	\checkmark
Resists bacteria	\checkmark		\checkmark	Ø	\checkmark
Repairable	\oslash	Ø	0	0	\checkmark
Inconspicuous joins	Ø	0	0	Ø	\checkmark
Resists stains	0	Ø		0	\checkmark



LOGO & TRADEMARK IS OWN BY RESPECTIVE SUPPLIER

OSGS ISSFA

